

Flush-mounted Delegate Unit



- ◆ Stylish Aluminum Extrusion
- ◆ Advanced Cat5e Cabling for Digital Series- parallel daisy-chain connection.
- ◆ Delegate unit can be linked anywhere withing the chain (Max 999 Delegate units)
- ◆ Features electrets condenser stem microphone
- ◆ "Talk" button to activate/deactivate microphone
- ◆ Stereo earphone jack*1; Rec*1
- ◆ Volume Control
- ◆ BXB gooseneck microphones adopt DIN type plug preventing bad contact of the connector
- ◆ Pluggable gooseneck microphone
- ◆ Illuminated red light ring for easy identification of speaker
- ◆ Quick access to "Chairman" mode
- ◆ Automatic test function
- ◆ Stem length: 43/48/56/70 cm (17", 18.9", 22", 27.6")With a built-in DSP chip, adjusting the audio output and sensitivity automatically
- ◆ MIC Auto-Off: 10-99 seconds

Information

BXB ELECTRONICS CO., LTD

TEL : +886(7) 970-3838

FAX : +886(7) 970-3883

Email: bxb@bxb.tw

<http://www.bxb.tw>

6F-1, No.288-5, Xinya Road,
Qianzhen District, Kaohsiung
City, Taiwan, R.O.C. 80673



TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥-50dB
Total Harmonic distortion	≤0.1%
S/N ratio	≥70dB
Voltage	DC 12V~18V
Connections	RJ-45 Jack x 2 , RJ-11 Jack x 1 (2.5M/20M Cat 5e)
Auto Gain Control (AGC)	-45 ~ 0dB
Earphone jack	3.5Ø Stereo
REC jack	3.5Ø Stereo
Height × Width × Depth	75 × 170 × 43 (mm)
Weight	346g w/o microphone
Material	Galvanized sheet steel
Surface	Aluminum extrusion