



Networked audio input panel - USB Type-C + 3.5 mm jack (4 CH)

Highlights:

- · Front USB type-C port
- Integrated Bluetooth receiver
- Internal mixing & DSP processing
- 4-channel Dante™/AES67

Product information:

The NWP400 is a Dante™/AES67 networked audio input panel, featuring a USB Type-C port, and an integrated Bluetooth receiver, which can be used to transmit audio signals in a Dante™ audio network.

Various further integrated DSP functions such as EQ, automatic gain control, and other device settings can be configured through the AUDAC Touch $^{\mathbb{M}}$.

The IP-based communication makes it future-proof while also being backward compatible with many existing products. Thanks to the limited PoE power consumption, NWP400 is compatible with any PoE network-based installation.

Besides the elegant design, the front panel is finished with high-quality fingerprint-resistant glass. The wall panels are compatible with standard EU-style in-wall boxes, making the wall panel the ideal solution for solid and hollow walls. Black and white color options are available to blend into any architectural design.



Certification:



Properties:

(a) Internal mixing & EQ

Additional Inputs:



System specifications:

Inputs		Bluetooth
		USB Type C (in)
Control		1 button - Bluetooth discoverable
Indicators		1 LED (RGB) - Bluetooth status
Configurable settings		IP settings
		Device name
		Gain
		DSP (EQ)
		Mixing
Configuration		Audac Touch™
Integrated DSP		Yes (EQ)
Automatic level control		Yes
Power	Supply	PoE powered (IEEE 802.3at)
Connectors		USB Type C (audio in)
		RJ45 (network + PoE)

Product Features:

Construction	ABS	
Front finish	Elegant ABS front panel with glass	
Dimensions	80 x 80 mm (W x H) (Remote wall panel)	
Colours	White (RAL9003) (DWP345/W)	
	Black (RAL9005) (DWP345/B)	
Compatible devices	Any Dante™/AES67 compatible audio device	
Installation standard	Compatible with EU installation materials	

Variants:

- NWP400/B Black version
- NWP400/W White version

