

# FCS 6315 Table-top Chairman Unit (W/ Voting, W/LCD)



- Features a built-in 2.5 inches high-fi loudspeaker and electrets condenser stem mic
- Provides Fixed/Pluggable gooseneck microphone for easier installation and maintenance
- Chairman Unit can be linked anywhere within the chain, max. up to **10** units
- Chairman features having "**Priority**" speak button to override delegate and the alarm sound when delegate-off
- Quick access to "**CHIARMAN**" mode
- Has dust/wind-proof functionality to prevent it from sound explosion
- Auto-Test functionality
- Provides Stem length: 43/56/70 cm
- All Mics have LED light to indicate ON/OFF status.
- Has LCD monitor display, the configurations can be set up, the speaking MIC ID No. & operating Modes can be displayed from it
- **3** colors indicator lamps indicate the status of Request, FIFO, and Override Mode
- Has a built-in Voting Functionality and the voting results can be displayed from LCD monitor
- 5 voting buttons can have functions as follows:
  - Present, YES(+), NO (-), ABSTAIN (X),(parliamentary voting)
  - Numerals: 1 to 5 (multiple choices or opinion poll voting)
  - Rating scale: --, - 0, +, ++ (audience response)
- Three (3) Images Auto-Tracing Modes can be configured from the Chairman Unit

## TECHNICAL SPECIFICATIONS

Frequency response	100HZ~16KHZ
Sensitivity	≥ -50dB
Total Harmonic distortion	≤ 0.1%
S/N ratio	≥ 70dB
Voltage	DC 12V~18V
<b>Build-in speaker</b>	
Unit size/Capacity/Max sound pressure	2.5"/0.5W/≥ 120dB
Speaking Indicator Lamp	3 colors LED Illustrated Red Ring Light
Connection	RJ-45 Jack x 2 (2.5M/20M Cat 5e)
Auto Gain Control (AGC)	-45 ~ 0dB
Earphone jack	3.5Ø Stereo
REC jack	3.5Ø Stereo
Height × Width × Depth	53.6 × 169.3 × 131.8 (mm)
Weight	877 g
Base	Zinc-Aluminum Alloy Diecast & Anti-slip mat
Top	ABS special plastic, Modern Black color

\*The appearance and specifications of all item are subject to change without notice