

HDC-715 Professional PTZ Camera

Ideal for Recording, Livestreaming, Video Conferencing, Remote Teaching & Training



Product Features

- ▶ Provides crystal-clear Full HD 1080p 60fps video solution.
- ▶ 20X optical zoom with 16X digital zoom, presenting precise and stable image.
- ▶ Equipped with 3G-SDI, HDMI, CVBS, Ethernet image outputs for transmitting uncompressed video signals.
- ▶ Supports PoE to supply power, simplifying the installation process and reducing the system costs.
- ▶ Presets 255 different locations and adjusts the pan, tilt, zoom, focus, exposure for quick capturing.
- ▶ Remote controls cameras via RS-232, RS485, and Ethernet with BXB software.
- ▶ Supports H.264 and H.265 for multiple streams.
- ▶ Intuitive and easily-operated Web-based interface for instantly monitoring camera images and controlling camera's direction, zoom, and other configurations.
- ▶ Built-in image flip and mirror functions for various installations, effective and convenient.



Hardware Specifications

Image Sensor	1/2.7" CMOS
Output Resolution	1080p 60/50 fps
Optical Zoom	20X
Pan Rotation	-170° (left) +170° (right)
Tilt Rotation	-30° (down) + 90° (up)
Video Output	3G-SDI, HDMI, CVBS, Ethernet (RJ45)
Network Protocol	RTSP/RTMP/ONVIF
PoE	Yes (IEEE 802.3at)
Remote Control	RS-232/485/Ethernet
Lens Focal Length	f=4.42mm~88.5mm
Pan Control Speed	1.7°~ 100°/sec
Tilt Control Speed	1.7°~ 69.9°/sec
Iris	F1.8 (wide) ~ F2.8 (tele)
Minimum Illumination	0.5 lux (F1.8, AGC ON)
Audio Input	Line In
Network Video Compress Format	H.264, H.265, MJPEG



Physical Specifications

Dimensions (WHD)	142 x 169 x 164 (mm)
Weight	1.35kg
Storage Temperature	-40°C to 60°C
Operation Temperature	-10°C to 40°C
Relative Humidity	45% ~ 70% (non-condensing)

BXB

BXB Electronics Co., Ltd.
(Headquarter in Kaohsiung, Taiwan)

A : Rm. 1, 6F., No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 80673, Taiwan (R.O.C.)

T : +886 7 9703838

F : +886 7 9703883

E : bxb@bxb.tw

www.bxb.tw