FCS-6380 **Control Software CCU**



Product Features

- ▶ Meeting control and settings: meeting modes, voting, recording, open mic qty, sound activation setting, camera preset point, and multi-screen switch/control.
- ▶ **Mobile control:** via TCP/IP control, you can use mobile devices such as smartphones/tablets for conferencing control and management. Web-browser management platform is also provided.
- ▶ Freely set the microphone ID and attendee identity: based on the microphone position and meeting purposes, you can change the microphone's ID and identity anytime. It enhances the efficacy of meeting registration and camera point preset-
- ▶ Microphone auto-off: set the auto-off time from 10-99 seconds to avoid attendees forgetting turning off the microphone.
- ▶ Adjust each microphone 's volume: adjust the volume of each microphone based on the speaking volume of the used attendee to keep the volume output consistent during the meeting.
- **Equipped with a service button:** press the button when the system has unusual conditions, the system would transmit the information about the user and system's condition back to BXB's headquarter. It efficiently realizes remote troubleshooting.



Hardware Specifications

Power Control Power button x 1

Power Connection DC12/7A MAX connector x 1 RS-232 DIN-9PIN connector x 2 USB 2.0 x 3 & USB 3.0 x 4 USB RJ-45 TCP/IP connector x 2 Internet

HDMI OUT x 2 Video Output Audio Interface LINE OUT x 1

LINE IN x 1 MIC IN x 1

Status Indication Indicator x 6 Abnormal Report Service button x 1



Physical Dimension

Unit Size (H*W*D) 44 x 431 x 205 (mm)

Cabinet 19" 1U

Weight 3Kg (power supply not included)

Temperature for -20°-80°C

Storage

Operating Tempera-0°-45°C

ture



Power Supply

External Power DC 12V 7A MAX

Supply

Voltage/Frequency 110/220V Total Power of Power 84W

Supply

Weight of Power

0.5Kg (power cord not included)

Supply



www.bxb.tw